

AC / GC2 code no. 12176


Technical specifications

Grammage	Caliper	Stiffness				
		L&W 5° md mNm	L&W 5° cd mNm	L&W 5° v(md x cd)	Taber 15° md mNm	Taber 15° cd mNm
g/m ²	µm					
200	310	11.7	5.8	8.2	5.9	2.7
215	340	15.0	7.6	10.7	7.7	3.6
230	370	18.4	9.5	13.2	9.8	4.9
245	400	22.0	11.5	15.9	11.9	6.0
265	440	28.5	14.3	20.2	15.0	7.6
275	460	32.0	15.8	22.5	16.7	8.5
290	490	37.0	18.6	26.2	19.7	10.0
305	520	41.6	21.4	29.8	22.7	11.6
325	560	49.0	25.2	35.1	27.4	14.1
350	615	60.0	31.5	43.5	34.1	17.6
375	670	73.0	39.0	53.4	41.9	21.6
400	725	88.2	46.7	64.2	50.8	26.3
425	780	105.5	55.7	76.7	60.8	31.4
450	840	125.0	65.1	90.2	71.8	37.1

Tolerance and properties not related to grammage

Property	Value	Tolerances	Test standard
Brightness top (% Elrepho)	90	- 1	ISO 2470-2
Grammage (g/m ²)		+/- 2%	EN ISO 536
Caliper (µm)		+/- 5%, > 350 g/m ² +/- 3%	EN 20534
Stiffness (mNm)		- 15%	DIN 53121
Stiff. L&W cd. (mNm)		- 15%	DIN 53121
Geometric Mean L&W (mNm)			DIN 53121
Stiffness (mNm)		- 15%	TAPPI T489
Stiffn. taber cd. (mNm)		- 15%	TAPPI T489
Recyclability		in terms of the norm	EN 13430
Biodegradability		in terms of the norm	EN 13432

Board structure



Virgin fibre 90% of total board (+/-5%)

Pigment coating 10% of total board (+/-5%)

¹Permissible: -15% of the target stiffness. This applies to 100% of all measured single values. The single value is a calculated average of five measurements per sheet. The stiffness has to be measured at both sides. The resulting average value is then the stiffness of the single sample. L&W 5° figures are binding, Taber figures are indicative. All figures mentioned above may be subject to technical changes.

AC / GC2 code no. 12176



Accurate – FOLBB Group’s “white” GC2 virgin fibre cartonboard – meets even the highest demands and puts the spotlight clearly on the benefits of the packed product. Accurate is therefore the best choice for demanding packaging where an outstanding visual impression is desired and/or it is essential for the packaging to be neutral in odour and taste.

If you are interested in ACCURATE or have any further questions, please contact sales.eerbeek@folbb.com

www.folbb.com

[General Terms of Trade](#)

This is a general recommendation. The cardboard should be checked for suitability before use.

Features

- impressive brightness
- attractive bright reverse side
- high smoothness
- brilliant gloss levels
- meets highest sensory requirements

Applications

- Dry Food
- Chilled Food (secondary packaging)
- Frozen Food
- Chocolate and Confectionery
- Food Service
- Pharma and Health Care
- Cosmetics and Personal Care

Mill Information

- comprehensive portfolio of virgin fibre cartonboard
- including qualities with special barriers against moisture and grease
- experienced, innovative production team and professional technical support
- strategically located to the Western, Eastern and Northern European markets
- flexible leadtimes and excellent service guaranteed

Certificates and statements

- ISO 9001
- ISO 14001
- ISO 22000 (incl. HACCP)
- ISO 50001
- FSC® (FSC® C170805)*
- PEFC (PEFC/04-31-3649)*
- HALAL
- Code of Conduct (CoC)
- EUTR - Timber Regulation No. 9952010 - (Declaration of origin)
- Food Safety Statement
- Law and Regulations Statement
- Chemical Statement
- Migration Statement (MOSH/MOAH)

Our products are also available with FSC® or PEFC certification on request.

More information about our products, including our certificates, are available on www.folbb.com